



product description:

the clamps are designed to attach steel pipes to the pad, using KPO 6 anchor or ZT 6 threaded rod and KPOZ 6 anchor to facilitate mounting, the clamp is provided with a groove for insertion; during mounting, it is not required to completely separate the top part of the clamp

the clamps are also available for systems maintaining functionality during a fire (see catalogue Systems with maintaining functionality during a fire)

material: steel

temperature resistance: -60 - +250 °C

classification according to EN 61386-25:12 for ZNCR: 3456210

fire resistance system: P 90-R, E 90, PS 90

certification: ČSN EN 61386-1 ed.2:09, ČSN EN 61386-25:12, ČSN EN 50102, ČSN 73 0895, DIN 4102-12, STN 92 0205

storage: ČSN EN 60721-3-1

surface: Bichromatic galvanized

item number	di (mm)	thread	weight 1 pc (kg)	package (pcs)	for pipes
5216 D_ZNCR	16	M6	0,01	1 / 50	6016E..., 6216E...
5220 D_ZNCR	20	M6	0,01	1 / 50	6020..., 6220...
5225 D_ZNCR	25	M6	0,02	1 / 50	6025..., 6225...
5232 D_ZNCR	32	M6	0,02	1 / 50	6032..., 6232...
5240 D_ZNCR	40	M6	0,02	1 / 50	6040..., 6240...
5250 D_ZNCR	50	M6	0,03	1 / 25	6050..., 6250...
5263 D_ZNCR	63	M6	0,07	1 / 25	6063..., 6263...