type number:	**NUV_S**
	NUV_ZM

product description:

Used to fasten covers to trays or accessories.

The fixing use the bolt NSM 6X10. To protect the cables, the bolt head is inside the cable tray.

It is possible to use the same bold used to fix the connection between the trays or accessories to fasten the cover fixture.

A minimum of 4 cover fixtures are required for 1 cover.

ZM surface finish cover fixture shall be used for ZM or F surface finish trays.

GMT surface finish bolts shall be used for ZM or F surface finish trays.

These items can also be ordered in a varnished version.

surface finish:

S - Pre-Galvanized steel according to ČSN EN 10346, ČSN EN 10143, zinc-layer 15-27 µm

ZM - Pre-Galvanized steel with admixture of magnesium and aluminum according to ČSN EN 10346, ČSN EN 10143, protective layer 18-31 µm (replacement of hot dip galvanizing)

sales amount: á 1 pc

meets the requirements: ČSN EN 61537:02

classification 🔥🔥:

ČSN 73 0895	P 90-R
DIN 4102-12	E 90
STN 92 0205	PS 90

Fire classification is depend on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire
Product approved for standard and non-standard constructions.

storage: ČSN EN 60721-3-1